

The Communicator II

The Communicator II can remotely view and control one or several EDXtreme instruments simultaneously via radio frequency. If the EDXtreme is not equipped with radio, then a RS-485 cable will be required between the EDXtreme and Communicator II. Information is easily sent to computer from a radio Communicator II via a serial cable. Data export pack which includes all cables and interfaces to connect from the unit directly into a PC. Mains Power supply, 100-240 VAC/5V to RS-232 for "Red" EDXtreme/Communicator II/ Quick check
 The communicator includes backlit display, AA-cell batteries, user manual and carry case.

Part Number	Product	List Price
AWT05-506447	Standard Communicator II handheld unit with radio & display backlight	£1,570
AWT05-509199	Standard Communicator II with radio, display backlight and 105dB audible alarm (NEW)	£2,030
AWT77-506958	Standard Communicator II with radio and alarm**	£2,860

** Not CE Approved

Accessories for Communicator

Part Number	Product	List Price
AWT05-509279	Data export pack which includes all cables and interfaces to connect from the unit directly into a PC.	£310
AWT25-501124	Mains Power supply, 100-240 VAC/5V to RS-232 for "Red" EDXtreme/Communicator II/Quick check	£405
36057-0071*	Communicator II to EDXtreme cable (LEMO to LEMO, RS-485 , 50-ft/15 m)	£250
AWT20-508223	Protective rubber sleeve, gray (recommended for outdoor applications)	£125

*Note: Special Lengths may be available per RFQ. Maximum length is 150 feet